




Universal scaler tip





Visual wear indicator

The Scorpion insert tip is coated with a 2µm thick and strong titanium nitride layer. To maintain efficiency and for patient comfort the insert has to be changed when the titanium coating has disappeared.

Very thin



Very powerful



Scorpion insert

Other insert

Scorpion reach inter-proximal space without difficulty



Scorpion insert

Other insert

A strong cavitation is guaranteed even with a low power scaling device.

Quality

USA and Canada Distributor

ISO 9001 & ISO 13485



PARADISE DENTAL TECHNOLOGIES

CE 0459

Made in France

8275 U.S. Hwy 10W • PO Box 17980 • Missoula, MT 59808
 406-626-4153 • Fax 406-626-4550 • 800-240-9895
 www.pdtdental.com

www.scorpion.fr

Scalers

Inserts

Technical data

EMS :

Scaling



B E M

Adaptable on EMS scalers for supragingival scaling.
Amplitude of vibration : 50 to 190 μm according the power.
Frequency : 29 KHz

Perio



E P E M

Adaptable on EMS scalers for subgingival scaling.
Amplitude of vibration : 20 to 130 μm according the power.
Frequency : 29 KHz

SATELEC / NSK piezo :

Scaling



B S A

Adaptable on Satelec scalers for supragingival scaling.
Amplitude of vibration : 50 to 230 μm according the power.
Frequency : 30 KHz

Perio



E P S A

Adaptable on Satelec scalers for subgingival scaling.
Amplitude of vibration : 50 to 130 μm according the power.
Frequency : 30 KHz

KAVO SONOsoft :

KAVO PIEZOlux :

Scaling



B K P

Adaptable on KAVO PIEZOlux and SONOsoft scalers for supragingival scaling.
Amplitude of vibration : 50 to 170 μm according the power.
Frequency : 29 KHz

Perio



E P K P

Adaptable on KAVO PIEZOlux and SONOsoft scalers for subgingival scaling.
Amplitude of vibration : 50 to 130 μm according the power.
Frequency : 29 KHz

SIRONA Sirosonic :

Scaling



B S I

Adaptable on Sirona Sirosonic scalers for supragingival scaling.
Amplitude of vibration : 50 to 200 μm according the power.
Frequency : 29 KHz

Perio



E P S I

Adaptable on Sirona Sirosonic scalers for subgingival scaling.
Amplitude of vibration : 50 to 150 μm according the power.
Frequency : 29 KHz

MECTRON :

Scaling



B M E C

Adaptable on Mectron scalers for supragingival scaling.
Amplitude of vibration : 50 to 170 μm according the power.
Frequency : 28 KHz

KAVO SONICflex :



A I R

Adaptable on KAVO SONICflex scalers.
Amplitude of vibration : 100 to 500 μm according the power.
Frequency : 6000 Hz

W&H - NSK Air :



A I R w

Adaptable on W&H and NSK Air scalers.
Amplitude of vibration : 100 to 500 μm according the power.
Frequency : 6000 Hz